

Speed, Resolution, and More Speed



5,315fps @ 2048x1536 | 16GPx/s throughput | 10,000fps @ 1512x1098



**i-SPEED 716R
shown in heavy
duty, rugged
environmental
package**

Choose from the sleek new instrumentation package or elect to upgrade your camera to the high-G rated rugged package with its environment resistant aluminum casing. When the fastest camera is required to capture the fastest events, the i-SPEED 7 is up to the task.



**The i-SPEED 716
camera is controlled
both by PC and
the new 7 Series
touchscreen CDUe**

FEATURES

- High resolution 2048x1536 pixel sensor (3.1MPx)
- 1080p resolution at 7,960 frames/second
- Up to 288 GB of on-board memory for long recordings
- Internal or external SSD drive for fast data transfer
- Microlens sensor for exceptional light sensitivity
- Wide Dynamic Range recording
- Global electronic shutter to 289 ns*
- 1 hour battery life
- Compatible with all Nikon F and Canon EF mount lenses
- Maximum frame rate – 1,000,000 fps
- Flexible frame synchronization from 10 Hz to 200 kHz
- Environmentally rugged package available
- 32 point integrated real-time health monitoring system
- Upgrade path between models

* Subject to export regulations, shorter shutter speeds are available by request. Contact iX Cameras for more information.

IMAGER

Sensor type	Custom CMOS
Sensor resolution	2048 x 1536 pixel
Sensor size	27.972 mm x 20.736 mm
Sensor diagonal	34.82 mm
Pixel size	13.5 µm
Bit depth	12 bit (36 bit color)
Light sensitivity Mono (Gain off/on)	4,000 / 32,000
Light sensitivity Color (Gain off/on)	1,000 / 8,000
Maximum frame rate	1,000,000 fps
Shutter type	Global Exposure
Shutter time, standard	1 µs minimum
Shutter time, fast mode	289 ns
WDR	Wide Dynamic Range

SYNCHRONIZATION and CAPTURE

Trigger	TTL T0 to 0-100%
Trigger modes	Circular, ROC, BROC
Sync	10 Hz - 200 kHz
Luminance histogram	Iris setting aid tool
i-CHEQ 360	Camera status LEDs
i-FOCUS	Focusing aid tool
i-EXPOSE	High/low exposure highlight
Control	PC or CDUE
IRIG input	IRIG – B to sub 1 µs
IRIG sync	Camera sync to IRIG
Internal memory	36 GB standard, upgrade to 288 GB

PHYSICAL and ENVIRONMENTAL

Dimensions	
Instrumentation package	
inches	14.3 (W) x 6.2 (H) x 6.2 (L)
mm	363 (W) x 157 (H) x 154 (L)
Rugged package	
inches	14.75 (W) x 6.0 (H) x 5.75 (L)
mm	374 (W) x 150 (H) x 143.5 (L)
Weight	18.7 lb (8.5 kg) with battery
Input voltage	12-36 V
Power consumption	150 W Nominal, 200 W Max
Mounting	¼x20 and 3/8x16 tripod plate
Battery	2x 14.4 V 90 Wh
Battery life	1 hour
Lens mount	Custom, swappable lens plate
EMC	EN55032-A, EN55024
Safety	BS EN61010-1 (camera), IEC60950 (PSU)
CE marking	EMC Directive (Camera), EMC Directive, LV Directive (PSU)
Lead free	RoHS Directive
WEEE	Compliant
IP rating	IP 20
Temperature °F	32 to 104 operation, -4 to 140 storage
Temperature °C	0 to 40 operation, -20 to 60 storage
Pressure	71 kpa to 106 kpa
Relative humidity	95% at 104°F non-condensing
G-shock, Instrumentation package	10 G
G-shock, Rugged package	30 G @ 11 ms IEC 68-2-27 Ea, 30 G @ 2 ms IEC 68-2-29 Eb
Power input connector	6 pin Lemo
Trigger input	BNC 75 Ω
Feature connector	18 pin Lemo, trigger in / sync / sync out / exposure out / remote power

CONNECTIVITY

Video outputs	2x HD-SDI, HDMI
USB	USB 3
Network	1 Gb RJ45
Video	IXV, AVI (compressed or uncompressed)
Image sequence	TIFF, JPG, RAW
Ethernet control	1 Gb
Remote control	Via supplied software

PC SOFTWARE

Standard control	Control ONE
Premium control	Control MULTI-DAQ
Editing	i-SPEED Movie Maker
Analysis	ProAnalyst® Lite by Xcitem
Viewer	i-SPEED Viewer
Utilities	i-SPEED Lens Calculator, i-SPEED Viewer
Software Developers Kit	C++, LabView
Synchronized data acquisition	USB DAQ, 8 options

PURCHASING OPTIONS

CDUE	Portable Control Unit
Sensor	Color / Mono
Memory	36 GB (std) / 72 GB / 96 GB / 144 GB / 288 GB
Shutter time	1 µs (std) / 289 ns (subject to export restrictions)
Internal SSD	500GB / 1TB / 2TB
External SSD	250GB / 500GB / 1TB / 2TB
Lens mounts	F mount (Nikkor D) / F mount (Nikkor G) C mount / EF mount
Package type	Instrumentation / Rugged
Warranty	1 yr (std) / 2 yr / 3 yr
Internal Batteries	Set of 2 batteries

FRAME RATES, RESOLUTION and DURATION

Frame Speed	Resolution	36GB	72GB	96GB	144GB	288GB
1,000	2048x1536	8.1 sec	16.2 sec	21.6 sec	32.4 sec	64.8 sec
2,000	2048x1536	4.1 sec	8.1 sec	10.8 sec	16.2 sec	32.4 sec
5,000	2048x1536	1.6 sec	3.2 sec	4.3 sec	6.5 sec	12.9 sec
5,315	2048x1536	1.5 sec	3.0 sec	4.1 sec	6.1 sec	12.2 sec
7,500	1736x1284	1.5 sec	3.1 sec	4.1 sec	6.2 sec	12.3 sec
7,960	1920x1080	1.5 sec	3.1 sec	4.1 sec	6.1 sec	12.2 sec
10,000	1512x1098	1.6 sec	3.1 sec	4.1 sec	6.2 sec	12.4 sec
15,000	1232x888	1.6 sec	3.1 sec	4.2 sec	6.3 sec	12.6 sec
20,000	1064x762	1.6 sec	3.2 sec	4.2 sec	6.4 sec	12.7 sec
30,000	840x624	1.6 sec	3.3 sec	4.4 sec	6.6 sec	13.1 sec
50,000	672x456	1.7 sec	3.4 sec	4.5 sec	6.7 sec	13.4 sec
100,000	672x216	1.8 sec	3.6 sec	4.7 sec	7.1 sec	14.2 sec
200,000	672x96	2.0 sec	4.0 sec	5.3 sec	8.0 sec	16.0 sec
300,000	672x54	2.4 sec	4.7 sec	6.3 sec	9.5 sec	18.9 sec
500,000	672x24	3.2 sec	6.4 sec	8.5 sec	12.8 sec	25.6 sec
750,000	336x24	4.3 sec	8.5 sec	11.4 sec	17.0 sec	34.1 sec
1,000,000	336x24	3.2 sec	6.4 sec	8.5 sec	12.8 sec	25.6 sec

Note: Other resolutions and speeds are available.



Specifications subject to change
Document: DS-716-1.7.20
Copyright © 2020 IX Cameras Ltd.

United Kingdom
Bradley House
Locks Hill
Rochford
Essex, SS4 1BB
T: +44 (0) 1702 540 669

United States
8 Cabot Rd.
Suite 1800
Woburn,
MA, 01801
T: 339 645 0778

China
Room 1402, Unit 65,
No 399 Hangting Road,
Oriental Hong Jing Garden,
ZhuQiao Town, Shanghai,
T: +86 186 215 60553

India
C-207, Twin Arcs
Legacy Life Spaces
Punwale Bazar
Punawale, Pune-411033
Maharashtra, India
T: +91 955 256 5021